

**Description**

MS20392-1R15 Straight Headed Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS203921R15
Minimum Qty (MOQ):	1
NSN:	5315-01-245-4179
Schedule B:	7319.40.9000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20392-1R15 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Chamfer Length:</b>	0.062 Inches Maximum
<b>Diameter:</b>	0.122 Inches Minimum And 0.124 Inches Maximum
<b>Under Head Length:</b>	0.413 Inches Minimum And 0.433 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.091 Inches Nominal
<b>Pin Chamfer Angle:</b>	14.5 Degrees Minimum And 15.5 Degrees Maximum
<b>Shear Strength:</b>	3080 Double Pound
<b>Pin Head Diameter:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Special Features:</b>	Shank End May Have Either A Chamfer Or Radius At The Option Of The Vendor
<b>Height:</b>	0.030 Inches Minimum And 0.062 Inches Maximum
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Chromium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-c-320 Cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Straight

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-1R15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.