

# P/N MS20392-2C63

Military-Fasteners.com

#### Description

length: 1-31/32", diameter: 3/16", straight drilled shank, cadmium plated steel alloy, MS20392 series pin

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | MS203922C63                 |
|-------------------------|-----------------------------|
| Minimum Qty (MOQ):      | 25                          |
| NSN:                    | 5315-00-777-6335            |
| Schedule B:             | 7319.90.0000                |
| ECCN:                   | 9A991                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



### P/N MS20392-2C63 Specifications

| Head Style:  | Pan No. 2 (r1 Not Required In Item Description)  |
|--|--|
| Chamfer Length:                                    | 0.062 Inches Maximum   |
| Diameter:  | 0.184 Inches Minimum And 0.186 Inches Maximum  |
| Under Head Length:                                 | 2.085 Inches Minimum And 2.105 Inches Maximum  |
| Hole Arrangement Style:                            | One End Drilled  |
| First Hole Diameter:                               | 0.066 Inches Minimum And 0.086 Inches Maximum  |
| Distance From Centerline Of Hole To End<br>Of Pin: | 0.088 Inches Minimum   |
| Hardness Rating:                                   | 26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| Pin Chamfer Angle:                                 | 14.5 Degrees Minimum And 15.5 Degrees Maximum  |
| Shear Strength:                                    | 4140 Double Pound  |
| Pin Head Diameter:                                 | 0.296 Inches Minimum And 0.328 Inches Maximum  |
| Special Features:                                  | Shank End May Have Either A Chamfer Or Radius At The Option Of The Vendor  |
| Height:  | 0.030 Inches Minimum And 0.062 Inches Maximum  |
| Material:  | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall  |
| Material Document And Classification:              | Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec<br>3rd Material Response Overall |
| Surface Treatment:                                 | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And<br>Classification:  | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| Style Designator:                                  | Straight   |
|  |  |

## How to Order

Order this straight headed pin from our inventory online by visiting <u>https://military-fasteners.com/pins/straight+headed+pins/MS20392-2C63</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.