

P/N MS20392-3C39

Description

length: 1-7/32", diameter: 1/4", straight drilled shank - cadmium plated steel alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS203923C39
Minimum Qty (MOQ): 10

NSN: 5315-00-770-9181

National Motor Freight: 095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N MS20392-3C39 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.062 Inches Nominal
Diameter:	0.246 Inches Minimum And 0.248 Inches Maximum
Under Head Length:	1.350 Inches Minimum And 1.370 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.076 Inches Minimum And 0.086 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.103 Inches Nominal
End Item Identification:	Mrap Rg-31 & Route Clearance Vehicle
lii End Item Identification:	Mrap Rg-31 & Route Clearance Vehicle; Medium Mine Protected Vehicle - Mmpv
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hardness Rating:	26.5 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	7360 Double Pound
Pin Head Diameter:	0.375 Inches Nominal
Height:	0.062 Inches Nominal
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material:	Steel Comp 4037 Or Steel Comp 4130 Or Steel Comp 8630 Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6758 Mil Spec 2nd Material Response Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

