

**Description**

length: 1-9/32", diameter: 1/4", straight drilled shank, cadmium plated steel alloy, MS20392 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS203923C41                                       |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5315-00-811-9105                                  |
| ECCN:                   | EAR99   |
| National Motor Freight: | 105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes |



\* See page 2 for technical characteristics

## P/N MS20392-3C41 Specifications

|  |   |
|--|---|
| <b>Head Style:</b>                                     | Pan No. 2 (r1 Not Required In Item Description)   |
| <b>Chamfer Length:</b>                                 | 0.062 Inches Nominal  |
| <b>Diameter:</b>                                       | 0.246 Inches Minimum And 0.248 Inches Maximum   |
| <b>Under Head Length:</b>                              | 1.412 Inches Minimum And 1.432 Inches Maximum   |
| <b>Hole Arrangement Style:</b>                         | One End Drilled   |
| <b>First Hole Diameter:</b>                            | 0.076 Inches Minimum And 0.086 Inches Maximum   |
| <b>Distance From Centerline Of Hole To End Of Pin:</b> | 0.103 Inches Nominal  |
| <b>End Item Identification:</b>                        | Mrap - Cougar   |
| <b>Hardness Rating:</b>                                | 26.5 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall   |
| <b>Pin Chamfer Angle:</b>                              | 15.0 Degrees Nominal  |
| <b>Shear Strength:</b>                                 | 7360 Double Pound   |
| <b>Pin Head Diameter:</b>                              | 0.375 Inches Nominal  |
| <b>Height:</b>   | 0.062 Inches Nominal  |
| <b>Material:</b>                                       | Steel Comp 4037 Or Steel Comp 4130 Or Steel Comp 8630 Overall   |
| <b>Material Document And Classification:</b>           | Ams 6300 Assn Std 1st Material Response Or Mil-s-6758 Mil Spec 2nd Material Response Or Mil-s-6050 Mil Spec 3rd Material Response Overall |
| <b>Surface Treatment:</b>                              | Cadmium And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b>  | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Style Designator:</b>                               | Straight  |

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C41> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.