

Description

length: 1-13/32", diameter: 1/4", straight, drilled shank, cadmium plated steel alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS203923C45 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5315-00-811-9107 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



P/N MS20392-3C45 Specifications

| | |
|--|---|
| Head Style: | Pan No. 2 (r1 Not Required In Item Description) |
| Chamfer Length: | 0.062 Inches Nominal |
| Diameter: | 0.246 Inches Minimum And 0.248 Inches Maximum |
| Under Head Length: | 1.537 Inches Minimum And 1.557 Inches Maximum |
| Hole Arrangement Style: | One End Drilled |
| First Hole Diameter: | 0.076 Inches Minimum And 0.086 Inches Maximum |
| Distance From Centerline Of Hole To End Of Pin: | 0.103 Inches Nominal |
| Hardness Rating: | 26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Pin Chamfer Angle: | 15.0 Degrees Nominal |
| Shear Strength: | 7360 Double Pound |
| Pin Head Diameter: | 0.375 Inches Nominal |
| Height: | 0.062 Inches Nominal |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall |
| Material Document And Classification: | Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Straight |

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.