

P/N MS20392-3C51

Description

Diameter: 1/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS203923C51

Minimum Qty (MOQ):

NSN: 5315-00-023-4253

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









^{*} See page 2 for technical characteristics

P/N MS20392-3C51 Specifications

ead Style:	Pan No. 2 (r1 Not Required In Item Description)
amfer Length:	0.062 Inches Nominal
ameter:	0.246 Inches Minimum And 0.248 Inches Maximum
der Head Length:	1.725 Inches Minimum And 1.745 Inches Maximum
le Arrangement Style:	One End Drilled
st Hole Diameter:	0.066 Inches Minimum And 0.086 Inches Maximum
stance From Centerline Of Hole To End Pin:	0.103 Inches Nominal
rdness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
n Chamfer Angle:	15.0 Degrees Nominal
ear Strength: 7	7360 Double Pound
n Head Diameter:	0.375 Inches Nominal
eight:	0.062 Inches Nominal
aterial:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
sterial Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
rface Treatment:	Cadmium Overall And Chromate Overall
rface Treatment Document And	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
yle Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C51 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.