

## P/N MS20392-3C63

### **Description**

length: 1-31/32", diameter: 1/4", straight drilled shank, cadmium plated steel alloy

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS203923C63

Minimum Qty (MOQ): 25

NSN: 5315-00-959-7692

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20392-3C63 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.062 Inches Nominal
Diameter:	0.246 Inches Minimum And 0.248 Inches Maximum
Under Head Length:	2.100 Inches Minimum And 2.120 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.066 Inches Minimum And 0.086 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.103 Inches Nominal
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	7360 Double Pound
Pin Head Diameter:	0.375 Inches Nominal
Height:	0.062 Inches Nominal
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

## **How to Order**

Order this straight headed pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C63">https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C63</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.