

Description

length: 2-7/32", diameter: 1/4", straight drilled shank - cadmium plated steel alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS203923C71
Minimum Qty (MOQ):	5
NSN:	5315-00-081-7019
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N MS20392-3C71 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.062 Inches Nominal
Diameter:	0.246 Inches Minimum And 0.248 Inches Maximum
Under Head Length:	2.350 Inches Minimum And 2.370 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.066 Inches Minimum And 0.086 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.103 Inches Nominal
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	15.0 Degrees Nominal
Pin Head Diameter:	0.375 Inches Nominal
Height:	0.062 Inches Nominal
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-8695 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-3C71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.