

Description

Diameter: 19/64", steel comp 4037or steel comp 4130or steel comp 8630 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS203924C35
Minimum Qty (MOQ):	5
NSN:	5315-00-023-4498
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N MS20392-4C35 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.078 Inches Nominal
Diameter:	0.309 Inches Minimum And 0.311 Inches Maximum
Under Head Length:	1.272 Inches Minimum And 1.292 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.096 Inches Minimum And 0.116 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.135 Inches Nominal
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	11500 Double Pound
Pin Head Diameter:	0.437 Inches Nominal
Height:	0.062 Inches Nominal
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-4C35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.