

## P/N MS20392-4C41

### **Description**

pan head, drilled, MS20392 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS203924C41

Minimum Qty (MOQ): 25

NSN: 5315-00-903-5944

National Motor Freight: 095190, Hardware, Noi Sub 9





<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20392-4C41 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.078 Inches Nominal
Diameter:	0.309 Inches Minimum And 0.311 Inches Maximum
Under Head Length:	1.459 Inches Minimum And 1.479 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.096 Inches Minimum And 0.116 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.135 Inches Nominal
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	11500 Double Pound
Pin Head Diameter:	0.437 Inches Nominal
Height:	0.062 Inches Nominal
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

## **How to Order**

Order this straight headed pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/straight+headed+pins/MS20392-4C41">https://military-fasteners.com/pins/straight+headed+pins/MS20392-4C41</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.