

**Description**

MS20392-4R39 Straight Headed Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS203924R39
Minimum Qty (MOQ):	2
NSN:	5315-01-374-5544
ECCN:	EAR99
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc

NO IMAGE  
AVAILABLE

## P/N MS20392-4R39 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Diameter:</b>	0.309 Inches Minimum And 0.311 Inches Maximum
<b>Under Head Length:</b>	1.209 Inches Minimum And 1.229 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.096 Inches Minimum And 0.116 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	1.113 Inches Nominal
<b>Shear Strength:</b>	191800 Double Pounds Per Square Inch
<b>Pin Head Diameter:</b>	0.437 Inches Nominal
<b>Height:</b>	0.062 Inches Nominal
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Chromium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-c-320 Class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Straight
<b>Specification/standard Data:</b>	96906-ms20392-4r39 Government Standard

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-4R39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.