

**Description**

MS20392-5C25 Straight Headed Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS203925C25
Minimum Qty (MOQ):	5
NSN:	5315-00-081-7032
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



NO IMAGE  
AVAILABLE

## P/N MS20392-5C25 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Chamfer Length:</b>	0.078 Inches Nominal
<b>Diameter:</b>	0.371 Inches Minimum And 0.373 Inches Maximum
<b>Under Head Length:</b>	0.959 Inches Minimum And 0.979 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.096 Inches Minimum And 0.116 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.135 Inches Nominal
<b>Hardness Rating:</b>	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Pin Chamfer Angle:</b>	15.0 Degrees Nominal
<b>Shear Strength:</b>	16580 Double Pound
<b>Pin Head Diameter:</b>	0.500 Inches Nominal
<b>Height:</b>	0.062 Inches Nominal
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
<b>Material Document And Classification:</b>	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Straight

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-5C25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.