

P/N MS20392-7P51

Description

MS20392-7P51STRAIGHT HEADED PIN

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS203927P51
Minimum Qty (MOQ):	1
NSN:	5315-01-329-4395
Schedule B:	7319.90.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N MS20392-7P51 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.078 Inches Nominal
Diameter:	0.495 Inches Minimum And 0.497 Inches Maximum
Under Head Length:	1.772 Inches Minimum And 1.792 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.096 Inches Minimum And 0.116 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.165 Inches Nominal
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	49080 Double Pound
Pin Head Diameter:	0.625 Inches Nominal
Height:	0.093 Inches Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Chromium Overall
Surface Treatment Document And Classification:	Qq-c-320,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting https://military-fasteners.com/pins/straight+headed+pins/MS20392-7P51 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.