

Description

Length: 1/4", aluminum alloy, roughly 16,000 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426A23 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-721-5208 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N MS20426A2-3 Specifications

| | |
|--|--|
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.061 Inches Minimum And 0.065 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.110 Inches Minimum And 0.118 Inches Maximum |
| Grip Length: | 0.084 Inches Minimum And 0.104 Inches Maximum |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A2-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.