

Description

Fastener Length: 7/8", MS20426 series rivet, roughly 1560 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426A314 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-808-8511 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N MS20426A3-14 Specifications

| | |
|--|--|
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.175 Inches Minimum And 0.183 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | Annealed Overall |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Qq-a-430,1100,h14 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A3-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.