

Description

Fastener Length: 7/8", MS20426 series rivet, roughly 1560 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426A314
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-808-8511
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20426A3-14 Specifications

Fastener Length:	0.875 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430,1100,h14 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A3-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.