

Description

Fastener Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426A320 |
| Minimum Qty (MOQ): | 200 EA |
| NSN: | 5320-00-660-1298 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20426A3-20 Specifications

| | |
|--|--|
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.179 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | Annealed Overall |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.