

Description

Fastener Length: 1/4, approx 5536 per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS20426A3-3.5](#)

SKU / Model:	MS20426A335
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-014-4328
National Motor Freight:	013630, Alum Rivets



P/N MS20426A3-3-5 Specifications

Fastener Length:	0.209 Inches Minimum And 0.229 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.169 Inches Minimum And 0.177 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	As Fabricated Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A3-3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.