

P/N MS20426A4-12

Description

Length: 3/4", diameter: 1/8", precision head, 1100-f aluminum, roughly 1025 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20426A412

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-264-3276

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N MS20426A4-12 Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426A4-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.