

Description

length: 1/8", diameter: 1/8", countersunk 100°, precision head - 1100-f aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426A42
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-577-8805



P/N MS20426A4-2 Specifications

Fastener Length:	0.125 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Grip Length:	0.083 Inches Nominal
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivetr, Solid, Countersunk 100 Degree, Precision Head
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Ams Qq-a-430 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.