

Description

length: 1/4", diameter: 1/8", countersunk, precision head, aluminum, roughly 2800 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426A44
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-619-0498
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS20426A4-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.