

P/N MS20426A4-7

Description

length: 7/16", diameter: 1/8", countersunk, precision head, aluminum, roughly 1825 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20426A47

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-543-3680

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets







^{*} See page 2 for technical characteristics

P/N MS20426A4-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Grip Length:	0.240 Nominal Mils And 0.260 Nominal Centimeters
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426A4-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.