

**Description**

length: 1", diameter: 5/32", countersunk, precision head, aluminum, roughly 490 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426A516
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-205-7659
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20426A5-16 Specifications

<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Grip Length:</b>	0.756 Nominal Mils And 0.776 Nominal Centimeters
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 1100 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.