

Description

Fastener Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426A620
Minimum Qty (MOQ):	100
NSN:	5320-00-684-9921
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20426A6-20 Specifications

Fastener Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Grip Length:	0.959 Nominal Mils And 0.979 Nominal Centimeters
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.