

**Description**

Fastener Length: 1-1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426A620         |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-684-9921    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N MS20426A6-20 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 1.240 Inches Minimum And 1.260 Inches Maximum                                  |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                       | 0.186 Inches Minimum And 0.190 Inches Maximum                                  |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                  | 0.349 Inches Minimum And 0.357 Inches Maximum                                  |
| <b>Grip Length:</b>                          | 0.959 Nominal Mils And 0.979 Nominal Centimeters                               |
| <b>Countersink Angle:</b>                    | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Material:</b>                             | Aluminum Alloy 1100 Overall  |
| <b>Material Document And Classification:</b> | Qq-a-430 Fed Spec Single Material Response Overall                             |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.