

**Description**

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20426A814                               |
| Minimum Qty (MOQ):      | 115 EA                                    |
| NSN:                    | 5320-01-282-4811                          |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

## P/N MS20426A8-14 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.865 Inches Minimum And 0.885 Inches Maximum                                  |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                       | 0.249 Inches Minimum And 0.253 Inches Maximum                                  |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                  | 0.472 Inches Minimum And 0.480 Inches Maximum                                  |
| <b>Grip Length:</b>                          | 0.480 Inches Minimum And 0.500 Inches Maximum                                  |
| <b>Countersink Angle:</b>                    | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Material:</b>                             | Aluminum Alloy 1100 Overall  |
| <b>Material Document And Classification:</b> | Qq-a-430 Fed Spec Single Material Response Overall                             |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426A8-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.