

# P/N MS20426AD10-8

## **Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20426AD108
Minimum Qty (MOQ):	80 EA
NSN:	5320-00-234-1511
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20426AD10-8 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.106 Inches Nominal
Shank Diameter:	0.312 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.560 Inches Minimum And 0.568 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 1100 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 5056 Overall

### **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8">https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8">https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8">https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8</a> and selecting the quantity you want then click "add to cart".