

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426AD108        |
| Minimum Qty (MOQ):      | 80 EA               |
| NSN:                    | 5320-00-234-1511    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | 9A991               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

# P/N MS20426AD10-8 Specifications

|                      |   |
|----------------------|---|
| Fastener Length:     | 0.500 Inches Nominal  |
| Head Style:          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| Head Height:         | 0.106 Inches Nominal  |
| Shank Diameter:      | 0.312 Inches Nominal  |
| Shank Style:         | Straight  |
| Head Major Diameter: | 0.560 Inches Minimum And 0.568 Inches Maximum   |
| Countersink Angle:   | 100.0 Degrees Nominal   |
| Material:            | Aluminum Alloy 1100 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 5056 Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.