

Description

Fastener Length: 63/64", roughly 75 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426AD1216 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-117-6865 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N MS20426AD12-16 Specifications

| | |
|---|---|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.374 Inches Minimum And 0.378 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.690 Inches Minimum And 0.698 Inches Maximum |
| Grip Length: | 0.438 Inches Nominal |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall Or Mil-c-5541,type 1,grade C,class 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD12-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.