

Description

Fastener Length: 1/4", roughly 16,000 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD23
Minimum Qty (MOQ):	100
NSN:	5320-00-117-6010
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20426AD2-3 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.061 Inches Minimum And 0.065 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.110 Inches Minimum And 0.118 Inches Maximum
Grip Length:	0.084 Nominal Mils And 0.104 Nominal Centimeters
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD2-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.