

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD312D
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-478-1041
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20426AD3-12D Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	Used On Fighter Aircraft F18 E/f
Grip Length:	0.704 Nominal Mils And 0.724 Nominal Centimeters
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet,solid,countersunk 100 Percent Precision Head,aluminum And Titanium Columbium Alloy
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-12D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.