



Military-Fasteners.com

P/N MS20426AD3-13D

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD313D
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-542-5547
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20426AD3-13D Specifications

Identification Code Color:	Yellow
Fastener Length:	0.813 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.098 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.184 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Rivet, Solid, Countersunk 100 Deg, Precision Head
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	T2117-t4 Al Alloy National Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-13D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.