

**Description**

Fastener Length: 15/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426AD315D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-563-2559
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20426AD3-15D Specifications

<b>Fastener Length:</b>	0.938 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.098 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.184 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	T2117-t4 National Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8624 Type II. Class 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.