

Description

Fastener Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426AD315D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-563-2559
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20426AD3-15D Specifications

Fastener Length:	0.938 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.098 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.175 Inches Minimum And 0.184 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Rivet, Solid
Material:	Aluminum Alloy Overall
Material Document And Classification:	T2117-t4 National Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8624 Type II. Class 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.