

**Description**

Fastener Length: 1"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426AD316D
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-477-5691
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20426AD3-16D Specifications

<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>End Item Identification:</b>	Used On Fighter Aircraft F18 E.f
<b>Grip Length:</b>	0.954 Nominal Mils And 0.974 Nominal Centimeters
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet,solid,countersunk 100 Percent Precision Head,aluminum And Titanium Columbium Alloy
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.