

Description

Length: 1-3/8", roughly 1000 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426AD322 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5320-01-007-8247 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20426AD3-22 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Fastener Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.175 Inches Minimum And 0.183 Inches Maximum |
| Grip Length: | 1.224 Nominal Mils And 1.244 Nominal Centimeters |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Ams 7222 Assn Std Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.