

Description

Length: 1/4", diameter: 3/32", countersunk precision head, aluminum alloy, roughly 5,000 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD34
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6938
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20426AD3-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	W/s:close In Weapon System (ciws-phalanx); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Def Comm Meteorol (an/tmq-028, An/tcc-76, An/tps-068, An-tcc-77); Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Support Equipment, B-1 Aircraft; Support Equipment, B-52 Aircraft; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Teammate, An/trq-32; Radar Set, An/pps-5b
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Criticality Code Justification:	Supp
Special Features:	Rivet Has 0.020 Inch Maximum Depth Dimple In Head, With A Maximum Diameter Of 0.030 Inches
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment:	Anodize Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Supplementary Features:	Flight Safety Critical

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.