

P/N MS20426AD3-4A

Description

MS20426AD3-4A Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20426AD34A

Minimum Qty (MOQ): 100

NSN: 5320-01-365-3217

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



^{*} See page 2 for technical characteristics

P/N MS20426AD3-4A Specifications

Fastener Length:	0.2400 Inches Minimum And 0.2600 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.0930 Inches Minimum And 0.0970 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1750 Inches Minimum And 0.1830 Inches Maximum
lii End Item Identification:	F-15 Eagle
Countersink Angle:	99.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2. Cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-4A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.