

**Description**

length: 5/16", diameter: 3/32", countersunk precision head, aluminum alloy, MS20426 series rivet, roughly 4,116 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426AD35
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6939
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N MS20426AD3-5 Specifications

<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>End Item Identification:</b>	W/s:teammate, An/trq-32; Radar Set, An/tpn-18; Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Communications Terminal, Satellite An/gsc-39(v)1; Traffic Jam, An/tlq-17a; Aircraft, Thunderbolt II, A-10; Support Equipment, B-52 Aircraft; Support Equipment, B-1 Aircraft; Missile, Advanced Medium Range Air-to-air (amraam)/aim120a
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.