P/N MS20426AD3-5.5

Description

length: 11/32", diameter: 3/32", countersunk precision head, 2117-t4 aluminum alloy, roughly 3790 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD355
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-044-1613
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

* See page 2 for technical characteristics

P/N MS20426AD3-5.5 Specifications

Fastener Length:	0.34375 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.09375 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.179 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426AD3-5.5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.