



★ FASTENERS

Military-Fasteners.com

P/N MS20426AD4-10

## Description

Length: 5/8", diameter: 1/8", countersunk precision head, aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20426AD410
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6955
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20426AD4-10 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Grip Length:</b>	0.427 Nominal Mils And 0.447 Nominal Centimeters
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.