

Description

length: 11/16", diameter: 1/8", countersunk precision head, aluminum alloy, roughly 1110 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD411
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-793-5513
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20426AD4-11 Specifications

Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Grip Length:	0.490 Nominal Mils And 0.510 Nominal Centimeters
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 1100 Overall Or Aluminum Alloy 5056 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430,alloy 1100 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 5056 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2024 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2017 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2117 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.