

**Description**

length: 11/16", diameter: 1/8", countersunk precision head, aluminum alloy, roughly 1110 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426AD411
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-793-5513
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



# P/N MS20426AD4-11 Specifications

<b>Fastener Length:</b>	0.678 Inches Minimum And 0.698 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Grip Length:</b>	0.490 Nominal Mils And 0.510 Nominal Centimeters
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 1100 Overall Or Aluminum Alloy 5056 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430,alloy 1100 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 5056 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2024 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2017 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 2117 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.