

Description

length: 1-1/8", diameter: 1/8", countersunk precision head, aluminum alloy, roughly 690 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD418
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6959
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20426AD4-18 Specifications

Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
End Item Identification:	W/s: F/a-18e/f Hornet Aircraft; Fms-aircraft, Hawkeye E-2c; Los Angeles Class Ssn (688); Aircraft, C-2a (reprocured); Missile, Advanced Medium Range Air-t0-air (amraam)/aim120a; Aircraft, Airlifter C-17a; Missile, Minuteman Lgm-30; Joint Stars Target Radar System; Missile, All-weather Ant-ship, Harpoon (agm-84); Engine, Aircraft, T56-a-7/15 (c-130b/e/h/n/p)
Grip Length:	0.927 Inches Minimum And 0.947 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.