

Description

length: 1/8", diameter: 1/8", countersunk precision head, 2117-t4 aluminum alloy, roughly 4970 pieces per pound, MS20426 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426AD42         |
| Minimum Qty (MOQ):      | 1 Pound             |
| NSN:                    | 5320-00-292-6713    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20426AD4-2 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.125 Inches Nominal   |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                       | 0.125 Inches Nominal   |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                  | 0.221 Inches Minimum And 0.229 Inches Maximum                                  |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal  |
| <b>Material:</b>                             | Aluminum Alloy 2117 Overall  |
| <b>Material Document And Classification:</b> | Qq-a-430 Fed Spec Single Material Response Overall                             |
| <b>Surface Treatment:</b>                    | Anodize Overall  |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.