

Description

Length: 3/16", diameter: 1/8", countersunk precision head, aluminum alloy, roughly 3700 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD43
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6948
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426AD4-3 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
End Item Identification:	W/s: Helicopter, Mh-53e; Missile, All-weather Anti-ship, Harpoon (agm-84); Switching Unit, Telephone, Auto; Helicopter, Advance Attack, Ah-1w; Helicopter, Search And Rescue, Hh-60h; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, C-2a (reprocured); Missile, Air-to-air, Phoenix (aim-54); Helicopter, Carrier Based Asw, Sh-60f
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.