

Description

length: 7/32", diameter: 1/8", countersunk precision head, aluminum alloy, roughly 3,150 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

MS20426AD4-3-5

SKU / Model:	MS20426AD435
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-317-0996
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426AD4-3.5 Specifications

Fastener Length:	0.209 Inches Minimum And 0.229 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-3.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.