

## P/N MS20426AD4-4A

### **Description**

flat countersunk head, roughly 2800 pieces per pound

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20426AD44A

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-609-6501

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20426AD4-4A Specifications

Fastener Length:	0.208 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Height:	0.042 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.225 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type Ii, Class 1, Clear Mil Spec Single Treatment Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A">https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A">https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A">https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A">https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-4A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/msa20426AD4-4A">https://military-fasteners.com/rivets/solid+rivets/msa20426AD4-4A</a> and selecting the property of t