

Description

MS20426AD4-5S Solid Rivet, roughly 2310 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD45S
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-535-1175
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20426AD4-5S Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
End Item Identification:	F-15e Wing
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall And Dichromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a, Clear Mil Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms20426 Government Specification

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-5S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.