



Military-Fasteners.com

**P/N MS20426AD4-5S**

## Description

MS20426AD4-5S Solid Rivet, roughly 2310 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20426AD45S
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-535-1175
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20426AD4-5S Specifications

<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>End Item Identification:</b>	F-15e Wing
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall And Dichromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541, Class 1a, Clear Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	96906-ms20426 Government Specification

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD4-5S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.